

METAPACE

Metapace L-2 – High-Performance Label Printer

www.metapace.com

Highlights

- Thermal transfer printer for professional label applications
- Fast printing at up to 152 mm per second
- Particularly large colour ribbon supply (up to 300m long)
- Includes serial, parallel and USB interfaces as standard
- Unpack and start printing: PSU, label roll, transfer ribbon and cleaning pen included

Technical specifications

Print

Printing method	Thermal transfer, direct thermal
Print width	25.4mm - 104mm
Print speed	152mm/sec.
Resolution	8 dots/mm (203dpi)
Consumables	Thermal paper labels, standard paper labels
Paper roll diameter	130mm (outer); 25.4mm ~ 38.1mm (inner)
Bar codes	Code 39, Code 93, Code 128, interleave 2 of 5, Coda Bar, UPC-A, UPC-E, EAN-8, EAN-13, Maxicode (2D), QR Code (2D), PDF 417 (2D), Data Matrix (2D)

Electronics

Emulation	SLCS, EPL II, ZPL II, ESC/POS
Sensor	Gap, Black Mark, Notch Sensor, Continuous Fan-Fold
Power supply	Input: AC 100V ~ 240V ± 10% (included); output: DC 24V 3.75A
Character set	Alphanumeric: 95 characters; extended character page: 128 x 22 international: 32 character; resident bitmap fonts: 10 True Type fonts: available
Reliability	MCBF: min. 12 months; auto-cutter: min. 6 months; TPH: min. 6 months

Specifics

Options	Auto-cutter, dispenser, Ethernet
---------	----------------------------------

Interfaces

I/F ports	RS232, parallel, USB (all standards)
-----------	--------------------------------------

Software

Drivers	Windows 2000, XP (32/64 Bit), 2003 Server (32/64 Bit), Vista (32/64 Bit), Windows 7 (32/64 Bit)
---------	---

Housing

Dimensions (WxHxD)	214x200x310mm
Colour	Black, white

Warranty

Period	24 months
--------	-----------

